

**ENVIRONMENTAL COMPLIANCE APPROVAL**

NUMBER 0177-DPHT59  
Issue Date: February 9, 2026

Miller Paving Limited  
281 Hillmount Rd, No. 101  
Markham, Ontario  
L6C 2S3

Site Location: Portable Crushing Plant

*You have applied under section 20.2 of Part II.1 of the Environmental Protection Act, R.S.O. 1990, c. E. 19 (Environmental Protection Act) for approval of:*

One (1) portable crushing plant operating in only one (1) of the two (2) following configurations at any given time, having a maximum throughput rate of 3000 tonnes of aggregate material per day, including the following processes and associated equipment exhausting into the air:

**Configuration 1**

- one (1) primary and one (1) secondary crushing unit, equipped with water spray system to control Fugitive Dust from crushing operations;
- one (1) primary and one (1) secondary screening unit;
- one (1) Tier 2 diesel-fired engine rated 910 kilowatts, discharging to the air through a stack having an exit diameter of 0.30 metre and a height of 4.1 metres above grade; and
- fugitive emissions from the handling, temporary storage and transfer of aggregate materials associated with the portable crushing operations;

**Configuration 2**

- one (1) primary and one (1) secondary crushing unit, equipped with water spray system to control Fugitive Dust from crushing operations;
- one (1) screening unit;
- one (1) Tier 2 diesel-fired engine rated 910 kilowatts, discharging to the air through a stack

having an exit diameter of 0.30 metre and a height of 4.1 metres above grade; and

- fugitive emissions from the handling, temporary storage and transfer of aggregate materials associated with the portable crushing operations;

all in accordance with the Environmental Compliance Approval Application dated November 27, 2024 and signed by H. William Kasper, Vice President, Engineering & Facilities, Miller Paving Limited., and all supporting information associated with the application including Emission Summary and Dispersion Modelling Report provided by BCX Environmental Consulting, dated November, 2024, emails dated November 21, December 5, and December 12, 2025, from Roxana Ungureanu of BCX Environmental Consulting, and November 28, 2025, from Tabitha Gaynor of BCX Environmental Consulting, Operations Summary Letter, dated December 4, 2025, signed by Bill Kasper of Miller Paving Limited, and the Acoustic Assessment Report prepared by HGC Noise Vibration Acoustics, dated August 28, 2025 and signed by Nik Bennett and Corey Kinart, P.Eng.

*For the purpose of this environmental compliance approval, the following definitions apply:*

1. "Acoustic Assessment Report" means the report, prepared in accordance with Publication NPC-233 submitted in support of the application, that documents all sources of noise emissions and Noise Control Measures present at the Plant. "Acoustic Assessment Report" also means the Acoustic Assessment Report prepared by HGC Noise Vibration Acoustics, dated August 28, 2025 and signed by Nik Bennett and Corey Kinart;
2. "Acoustic Barrier" means a barrier or berm positioned such that it completely interrupts the line of sight between the Plant and the noise sensitive Points of Reception continuous without holes, gaps and other penetrations, and having surface mass of at least 20 kilograms per square metres;
3. "Approval" means this Environmental Compliance Approval, including the application and all supporting documentation;
4. "Best Management Practices Plan" or BMPP means the document titled "Dust Management Plan" dated November 26, 2025, prepared by the Miller Group Inc. and received as part of the email dated December 5, 2025 from Roxana Ungureanu of BCX Environmental Consulting;
5. "Class 1 Area" means an area with an acoustical environment typical of a major population centre, where the background sound level is dominated by the activities of people, usually road traffic, often referred to as "urban hum";
6. "Class 2 Area" means an area with an acoustical environment that has qualities representative of both Class 1 and Class 3 areas:
  1. sound levels characteristic of Class 1 during daytime (07:00 to 19:00 or to 23:00 hours); and
  2. low evening and night background sound level defined by natural environment and infrequent human activity starting as early as 19:00 hours (19:00 or 23:00 to 07:00 hours);

7. "Class 3 Area" means a rural area with an acoustical environment that is dominated by natural sounds having little or no road traffic, such as:
  1. a small community;
  2. agricultural area;
  3. a rural recreational area such as a cottage or a resort area; or
  4. a wilderness area;
8. "Company" means Miller Paving Limited that is responsible for the construction or operation of the Plant and includes any successors and assigns;
9. "Director" means any Ministry employee appointed by the Minister pursuant to Section 5 of the EPA;
10. "District Manager" means the District Manager of the appropriate local district office of the Ministry, at the geographic location where the Plant is operated;
11. "EPA" means the Environmental Protection Act, R.S.O. 1990, c.E.19, as amended;
12. "Equipment" means the equipment and processes described in the Company's application, this Approval and in the supporting documentation referred to herein, to the extent approved by this Approval;
13. "Fugitive Dust" means any solid particulate matter that becomes airborne, other than that emitted from an exhaust stack, directly or indirectly as a result of the activities of any person;
14. "Manual" means a document or a set of documents that provides written instructions to staff of the Company;
15. "Method 22" means the United States Environmental Protection Agency document titled "Method 22 - Visual Determination of Fugitive Emissions from Material Sources and Smoke Emissions from Flares" dated January 14, 2019, as amended;
16. "Minister" means the Minister of the Environment, Conservation and Parks or such other member of the Executive Council as may be assigned the administration of the EPA under the Executive Council Act;
17. "Ministry" means the ministry of the Minister;
18. "Noise Control Measures" means measures to reduce the noise emissions from the Plant / Equipment including, but not limited to, silencers, acoustic louvers, enclosures, absorptive treatment, plenums and barriers, described in the Company's application, this Approval and in the supporting documentation referred to herein, to the extent approved by this Approval;

19. "Operations Summary Letter" means the letter from Miller Paving Limited, dated December 4, 2025, signed by Bill Kasper and forms the part of this Approval;
20. "Plant" means the entire portable crushing and screening operations, incorporating the Equipment;
21. "Point of Reception" means a Point of Reception as defined in Publication NPC-300;
22. "Publication NPC-233" means the Ministry Publication NPC-233 "Information to be Submitted for Approval of Stationary Sources of Sound" , October 1995, as amended;
23. "Publication NPC-300" means the Ministry Publication NPC-300, "Environmental Noise Guideline, Stationary and Transportation Sources – Approval and Planning, Publication NPC-300", August, 2013, as amended;
24. "Raw Materials" means unprocessed materials that are received by the Plant and fed to the crushing unit; and
25. "Sensitive Receptor" means any location where routine or normal activities occurring at reasonably expected times would experience adverse effect(s) from discharges from the Plant to the atmosphere, including one or a combination of:
  - a. private residences or public facilities where people sleep (e.g.: single and multi-unit dwellings, nursing homes, hospitals, trailer parks, camping grounds, etc.),
  - b. institutional facilities (e.g.: schools, churches, community centres, day care centres, recreational centres, etc.),
  - c. outdoor public recreational areas (e.g.: trailer parks, play grounds, picnic areas, etc.), and
  - d. other outdoor public areas where there are continuous human activities (e.g.: commercial plazas and office buildings).

*You are hereby notified that this environmental compliance approval is issued to you subject to the terms and conditions outlined below:*

## **TERMS AND CONDITIONS**

### **1. Noise Emissions**

1. The Company shall, at all times, ensure that the noise emissions from the Plant comply with the limits determined in accordance with Ministry Publication NPC-300.

### **2. Time Restrictions**

1. The Company shall ensure that, at any one site, the Plant is not operated more than sixty (60) calendar days per year.
2. The Company shall ensure that the Acoustic Barrier, when required, is erected within 7 working days of start-up of the Plant and until that time, the Plant operations shall be restricted to the daytime hours of 7 a.m. to 7 p.m., Monday to Friday.

### **3. Minimum Separation Distance(s)**

1. The Company shall ensure a minimum separation distance of 470 meters between the Plant and the nearest Sensitive Receptor.
2. The Company shall ensure a minimum separation distance is maintained between the Plant and the nearest Point of Reception as specified in Schedule B.

### **4. Noise Control Measures**

1. The Company shall ensure that the Acoustic Barrier, when required, is implemented at all times during the operation of the Plant.
2. The Company shall ensure that the Acoustic Barrier, when required, is continuous without holes, gaps or other penetrations, and having a surface mass density of at least 20 kilograms per square metre, and that it will be positioned in between the Plant and the Points of Reception that require shielding in such a way that the distance from the Acoustic Barrier to the Plant is not greater than 30 metres as depicted in figures 1 and 2 of the Acoustic Assessment Report. The minimum dimensions of the Acoustic Barrier shall be minimum 6, 8 or 9 metres high, and at least 45 metres or 60 metres long, as indicated in Schedule B.
3. The Company shall ensure that the Acoustic Barrier, when required, is properly maintained and continues to provide the acoustical performance outlined in the Acoustic Assessment Report.

## **5. Operation and Maintenance**

1. The Company shall ensure that the Plant/Equipment is properly operated and maintained at all times. The Company shall:
  - a. prepare, not later than three (3) months after the date of this Approval, and update, as necessary, a Manual outlining the operating procedures and a maintenance program for the Plant/Equipment, including:
    - i. routine operating and maintenance procedures in accordance with good engineering practices and as recommended by the Equipment suppliers;
    - ii. emergency procedures;
    - iii. procedures for determining the separation distances to the nearest Point of Reception and the nearest Sensitive Receptors;
    - iv. procedures for determining the type of Raw Materials;
    - v. all appropriate measures to minimize noise and dust emissions from all potential sources;
    - vi. all necessary procedures and undertaken measures to ensure compliance with Condition 6.4;
    - vii. the frequency of inspection and maintenance of water spray systems controlling Fugitive Dust emissions from the Equipment; and
    - viii. procedures for any record keeping activities relating to operation and maintenance of the Plant/Equipment;
  - b. implement the recommendations of the Manual; and
  - c. retain, for a minimum of two (2) years from the date of their creation, all records on the maintenance, repair and inspection of the Equipment, and make these records available for review by staff of the Ministry upon request.
2. The Company shall ensure that the only Raw Materials that are processed by the Equipment are limestone, mixed stone/gravel, granite, trap rock, recycled concrete, and reclaimed asphalt pavement.
3. The Plant is approved to operate from February through December.
4. The Company shall ensure that no Plant other than the Plant approved under this Approval is operated concurrently at any one site.

## **6. Fugitive Dust Control**

1. The Company shall implement the BMPP for the control of Fugitive Dust from any potential sources of Fugitive Dust emissions resulting from the operations of the Plant at each operating site.
2. The Company shall update the BMPP for each operating site as necessary or at the direction of the District Manager.
3. The Company shall retain on each operating site the latest version of the BMPP and shall provide it to any employee or agent of the Ministry upon request.
4. The Company shall ensure that visible Fugitive Dust emissions from activities where material is dropped:
  - a. will not extend more than 30 metres in any direction from the activities, excluding no more than 6 minutes in any hour; and
  - b. will not extend, at any time, beyond the separation distance as specified in Condition 3.1.
5. The Company shall determine visible Fugitive Dust emissions, referred to in Condition 6.4, using Method 22, at the closest practical observation location as described in Method 22.

## **7. Marking of Portable Plant**

1. The Company shall post a legible sign in a location which is accessible to the public, clearly identifying:
  - a. the Company name;
  - b. the number of this Approval;
  - c. a brief description of the nature of the operation;
  - d. a Company contact name and telephone number for the public to provide comments;
  - e. hours of operation; and
  - f. length of time the Company intends to operate the Plant at that location.

## **8. Keeping a Valid Approval**

1. The Company shall ensure that a copy of this Approval, as well as any subsequent Amended Approvals or Notices that amend this Approval, are available for inspection by a Provincial Officer at each site where the Plant is operated.

## **9. Record Retention**

1. The Company shall retain, for a minimum of two (2) years from the date of their creation, all records and information related to or resulting from the recording activities required by this Approval, and make these records available for review by staff of the Ministry upon request. The Company shall retain:
  - a. all records on the maintenance, repair and inspection of the Equipment;
  - b. all records on the daily operation of the Plant/Equipment, including:
    - i. daily production rate;
    - ii. daily start-up and shut-down times of the Plant/Equipment;
    - iii. the type of Raw Materials;
  - c. all records of any upset conditions associated with the operation of the Plant/Equipment;
  - d. all records on the environmental complaints, including:
    - i. a description, time, date and location of each incident;
    - ii. operating conditions (e.g. upset conditions, etc.) at the time of the incident;
    - iii. wind direction and other weather conditions at the time of the incident;
    - iv. the name(s) of Company personnel responsible for handling the incident;
    - v. the cause of the incident;
    - vi. the Company response to the incident; and
    - vii. a description of the measures taken to address the cause of the incident and to prevent a similar occurrence in the future, and the outcome of the measures taken.

## **10. Notification of Complaints**

1. The Company shall notify the District Manager, in writing, of each environmental complaint within two (2) business days of the complaint. The notification shall include:
  - a. a description of the nature of the complaint;
  - b. the time, date and location of the incident;
  - c. the wind direction and other weather conditions at the time of the incident; and
  - d. the name(s) of Company personnel responsible for handling the incident.



## **11. Change of Owner**

1. The Company shall notify the Director and the District Manager, in writing, of any of the following changes within thirty (30) days of the change occurring:
  - a. change of owner or operating authority, or both;
  - b. change of address of owner or operating authority or address of new owner or operating authority;
  - c. change of partners where the owner is or at any time becomes a partnership, and a copy of the most recent declaration filed under the Business Names Act, R.S.O. 1990, c. B.17, as amended, shall be included in the notification;
  - d. change of name of the corporation where the owner is or at any time becomes a corporation, and a copy of the most current information filed under the Corporations Information Act, R.S.O. 1990, c. C.39, as amended, shall be included in the notification.
2. The Company shall notify any succeeding new owner, in writing, of the existence of this Approval, as well as any subsequent Amended Approvals or Notices that amend this Approval and, shall forward a copy of such a notice to the Director and the District Manager together with the notification required under Condition 12.1.

## **12. Relocation**

1. The Company shall notify the District Manager, in writing, at least ten (10) business days in advance of any intended location of the Plant at each operating site, by submitting a completed Form 1, outlined in Schedule A.

## **SCHEDULE A**

### **Form 1: Notice of Relocation For Portable Equipment**

1. Owner and/or Operator
  - a. Company name :
  - b. Contact person :
  - c. Telephone number :
2. Proposed Location
  - a. Municipality/Township:
  - b. Site information (complete as applicable):

- i. Civic address:
- ii. Lot/Concession:
- iii. Geo Reference (UTM):

3. Operation

- a. Date of commencement and completion of operation: from                      to
- b. Hours of operation: from                      to
- c. Identification of the Plant and the operating scenario as defined in Schedules B of this Approval
- d. Maximum processing rate (tonnes/hour):
- e. Type of material to be processed:

Please attach the following:

- 1. A copy of the Approval.
- 2. A copy of the BMPP for the control of Fugitive Dust.
- 3. Documentation that confirms the type of Raw Materials to be processed.
- 4. A plot plan or sketch of the proposed location showing the following:
  - a. the entire operating site
  - b. distance between the Equipment and the nearest off-property Point of Reception
  - c. distance between the Equipment and the nearest Sensitive Receptor
  - d. land use within the minimum separation distances from the Equipment specified in Condition No. 3 of this Approval.

## SCHEDULE B

### Minimum Required Separation Distances from the Plant to the Points of Reception

**Table 1: Operating Scenario 1 - Primary Crusher, Screen and Secondary Crusher without Acoustic Barrier**

| Publication<br>NPC-300<br>Acoustical Area | Time of Operation           | Sound Level<br>Limit (dBA) | Minimum Separation Distance<br>(metres) |
|-------------------------------------------|-----------------------------|----------------------------|-----------------------------------------|
| Class 1                                   | Day (7 a.m. to 7 p.m.)      | 50                         | 875                                     |
| Class 1                                   | Evening (7 p.m. to 11 p.m.) | 50                         | 875                                     |
| Class 1                                   | Night (11 p.m. to 7 a.m.)   | 45                         | 1,350                                   |
| Class 2                                   | Day (7 a.m. to 7 p.m.)      | 50                         | 875                                     |
| Class 2                                   | Evening (7 p.m. to 11 p.m.) | 45                         | 1,350                                   |
| Class 2                                   | Night (11 p.m. to 7 a.m.)   | 45                         | 1,350                                   |
| Class 3                                   | Day (7 a.m. to 7 p.m.)      | 45                         | 1,350                                   |
| Class 3                                   | Evening (7 p.m. to 11 p.m.) | 40                         | 2,000                                   |
| Class 3                                   | Night (11 p.m. to 7 a.m.)   | 40                         | 2,000                                   |

**Table 2: Operating Scenario 2 - Primary Crusher, Screen and Secondary Crusher with 6 metre high, 45 metre long Acoustic Barrier**

| Publication<br>NPC-300<br>Acoustical Area | Time of Operation           | Sound Level<br>Limit (dBA) | Minimum Separation Distance<br>(metres) |
|-------------------------------------------|-----------------------------|----------------------------|-----------------------------------------|
| Class 1                                   | Day (7 a.m. to 7 p.m.)      | 50                         | 575                                     |
| Class 1                                   | Evening (7 p.m. to 11 p.m.) | 50                         | 575                                     |
| Class 1                                   | Night (11 p.m. to 7 a.m.)   | 45                         | 940                                     |
| Class 2                                   | Day (7 a.m. to 7 p.m.)      | 50                         | 575                                     |
| Class 2                                   | Evening (7 p.m. to 11 p.m.) | 45                         | 940                                     |
| Class 2                                   | Night (11 p.m. to 7 a.m.)   | 45                         | 940                                     |
| Class 3                                   | Day (7 a.m. to 7 p.m.)      | 45                         | 940                                     |
| Class 3                                   | Evening (7 p.m. to 11 p.m.) | 40                         | 1,390                                   |
| Class 3                                   | Night (11 p.m. to 7 a.m.)   | 40                         | 1,390                                   |

**Table 3: Operating Scenario 3 - Primary Crusher, Screen and Secondary Crusher with 8 metre high, 45 metre long Acoustic Barrier**

| Publication<br>NPC-300<br>Acoustical Area | Time of Operation           | Sound Level<br>Limit (dBA) | Minimum Separation Distance<br>(metres) |
|-------------------------------------------|-----------------------------|----------------------------|-----------------------------------------|
| Class 1                                   | Day (7 a.m. to 7 p.m.)      | 50                         | 455                                     |
| Class 1                                   | Evening (7 p.m. to 11 p.m.) | 50                         | 455                                     |
| Class 1                                   | Night (11 p.m. to 7 a.m.)   | 45                         | 875                                     |
| Class 2                                   | Day (7 a.m. to 7 p.m.)      | 50                         | 455                                     |

|         |                             |    |       |
|---------|-----------------------------|----|-------|
| Class 2 | Evening (7 p.m. to 11 p.m.) | 45 | 875   |
| Class 2 | Night (11 p.m. to 7 a.m.)   | 45 | 875   |
| Class 3 | Day (7 a.m. to 7 p.m.)      | 45 | 875   |
| Class 3 | Evening (7 p.m. to 11 p.m.) | 40 | 1,375 |
| Class 3 | Night (11 p.m. to 7 a.m.)   | 40 | 1,375 |

**Table 4: Operating Scenario 4 - Primary Crusher, Screen and Secondary Crusher with 9 metres high, 45 metre long Acoustic Barrier**

| Publication<br>NPC-300<br>Acoustical Area | Time of Operation           | Sound Level<br>Limit (dBA) | Minimum Separation Distance<br>(metres) |
|-------------------------------------------|-----------------------------|----------------------------|-----------------------------------------|
| Class 1                                   | Day (7 a.m. to 7 p.m.)      | 50                         | 385                                     |
| Class 1                                   | Evening (7 p.m. to 11 p.m.) | 50                         | 385                                     |
| Class 1                                   | Night (11 p.m. to 7 a.m.)   | 45                         | 800                                     |
| Class 2                                   | Day (7 a.m. to 7 p.m.)      | 50                         | 385                                     |
| Class 2                                   | Evening (7 p.m. to 11 p.m.) | 45                         | 800                                     |
| Class 2                                   | Night (11 p.m. to 7 a.m.)   | 45                         | 800                                     |
| Class 3                                   | Day (7 a.m. to 7 p.m.)      | 45                         | 800                                     |
| Class 3                                   | Evening (7 p.m. to 11 p.m.) | 40                         | 1,320                                   |
| Class 3                                   | Night (11 p.m. to 7 a.m.)   | 40                         | 1,320                                   |

**Table 5: Operating Scenario 5 - Primary Crusher & Screen and Secondary Crusher & Screen without Acoustic Barrier**

| Publication<br>NPC-300<br>Acoustical Area | Time of Operation           | Sound Level<br>Limit (dBA) | Minimum Separation Distance<br>(metres) |
|-------------------------------------------|-----------------------------|----------------------------|-----------------------------------------|
| Class 1                                   | Day (7 a.m. to 7 p.m.)      | 50                         | 945                                     |
| Class 1                                   | Evening (7 p.m. to 11 p.m.) | 50                         | 945                                     |
| Class 1                                   | Night (11 p.m. to 7 a.m.)   | 45                         | 1,450                                   |
| Class 2                                   | Day (7 a.m. to 7 p.m.)      | 50                         | 945                                     |
| Class 2                                   | Evening (7 p.m. to 11 p.m.) | 45                         | 1,450                                   |
| Class 2                                   | Night (11 p.m. to 7 a.m.)   | 45                         | 1,450                                   |
| Class 3                                   | Day (7 a.m. to 7 p.m.)      | 45                         | 1,450                                   |
| Class 3                                   | Evening (7 p.m. to 11 p.m.) | 40                         | 2,160                                   |
| Class 3                                   | Night (11 p.m. to 7 a.m.)   | 40                         | 2,160                                   |

**Table 6: Operating Scenario 6 - Primary Crusher & Screen and Secondary Crusher & Screen with 6 metres high, 60 metre long Acoustic Barrier**

| Publication<br>NPC-300<br>Acoustical Area | Time of Operation           | Sound Level<br>Limit (dBA) | Minimum Separation Distance<br>(metres) |
|-------------------------------------------|-----------------------------|----------------------------|-----------------------------------------|
| Class 1                                   | Day (7 a.m. to 7 p.m.)      | 50                         | 610                                     |
| Class 1                                   | Evening (7 p.m. to 11 p.m.) | 50                         | 610                                     |

|         |                             |    |       |
|---------|-----------------------------|----|-------|
| Class 1 | Night (11 p.m. to 7 a.m.)   | 45 | 990   |
| Class 2 | Day (7 a.m. to 7 p.m.)      | 50 | 610   |
| Class 2 | Evening (7 p.m. to 11 p.m.) | 45 | 990   |
| Class 2 | Night (11 p.m. to 7 a.m.)   | 45 | 990   |
| Class 3 | Day (7 a.m. to 7 p.m.)      | 45 | 990   |
| Class 3 | Evening (7 p.m. to 11 p.m.) | 40 | 1,510 |
| Class 3 | Night (11 p.m. to 7 a.m.)   | 40 | 1,510 |

**Table 7: Operating Scenario 7 - Primary Crusher & Screen and Secondary Crusher & Screen with 8 metres high, 60 metre long Acoustic Barrier**

| Publication<br>NPC-300<br>Acoustical Area | Time of Operation           | Sound Level<br>Limit (dBA) | Minimum Separation Distance<br>(metres) |
|-------------------------------------------|-----------------------------|----------------------------|-----------------------------------------|
| Class 1                                   | Day (7 a.m. to 7 p.m.)      | 50                         | 500                                     |
| Class 1                                   | Evening (7 p.m. to 11 p.m.) | 50                         | 500                                     |
| Class 1                                   | Night (11 p.m. to 7 a.m.)   | 45                         | 940                                     |
| Class 2                                   | Day (7 a.m. to 7 p.m.)      | 50                         | 500                                     |
| Class 2                                   | Evening (7 p.m. to 11 p.m.) | 45                         | 940                                     |
| Class 2                                   | Night (11 p.m. to 7 a.m.)   | 45                         | 940                                     |
| Class 3                                   | Day (7 a.m. to 7 p.m.)      | 45                         | 940                                     |
| Class 3                                   | Evening (7 p.m. to 11 p.m.) | 40                         | 1,490                                   |
| Class 3                                   | Night (11 p.m. to 7 a.m.)   | 40                         | 1,490                                   |

**Table 8: Operating Scenario 8 - Primary Crusher & Screen and Secondary Crusher & Screen with 9 metres high, 60 metre long Acoustic Barrier**

| Publication<br>NPC-300<br>Acoustical Area | Time of Operation           | Sound Level<br>Limit (dBA) | Minimum Separation Distance<br>(metres) |
|-------------------------------------------|-----------------------------|----------------------------|-----------------------------------------|
| Class 1                                   | Day (7 a.m. to 7 p.m.)      | 50                         | 420                                     |
| Class 1                                   | Evening (7 p.m. to 11 p.m.) | 50                         | 420                                     |
| Class 1                                   | Night (11 p.m. to 7 a.m.)   | 45                         | 880                                     |
| Class 2                                   | Day (7 a.m. to 7 p.m.)      | 50                         | 420                                     |
| Class 2                                   | Evening (7 p.m. to 11 p.m.) | 45                         | 880                                     |
| Class 2                                   | Night (11 p.m. to 7 a.m.)   | 45                         | 880                                     |
| Class 3                                   | Day (7 a.m. to 7 p.m.)      | 45                         | 880                                     |
| Class 3                                   | Evening (7 p.m. to 11 p.m.) | 40                         | 1,460                                   |
| Class 3                                   | Night (11 p.m. to 7 a.m.)   | 40                         | 1,460                                   |

**Note**

The Acoustic Barrier shall have a height of not less than 6, 8 or 9 metres above local grade, in accordance with each operating scenario in Tables 1 through 8 above. The Acoustic Barrier shall have a length not less than 45 or 60 metres, depending on operating scenario, and must break the line-of-sight between the Plant and all Points of Reception that require shielding. The top of the Acoustic Barrier

must be located at a distance of no more than 30 metres from the nearest surge bin as depicted in figures 1 and 2 of the Acoustic Assessment Report.

*The reasons for the imposition of these terms and conditions are as follows:*

1. Conditions No. 1 to 8 are included to provide the minimum performance requirements considered necessary to prevent an adverse effect resulting from the operation of the Plant/Equipment and to emphasize that the Plant/Equipment must be maintained and operated according to a procedure that will result in compliance with the EPA, the regulations and this Approval.
2. Condition No. 9 is included to require the Company to keep records and to provide information to the Ministry so that compliance with the EPA, the regulations and this Approval can be verified.
3. Conditions No. 10 to 12 are included to require the Company to notify/report to the Ministry so that compliance with the EPA, the regulations and this Approval can be verified.

In accordance with Section 139 of the *Environmental Protection Act*, you may by written notice served upon me, the Ontario Land Tribunal and in accordance with Section 47 of the *Environmental Bill of Rights*, 1993, the Minister of the Environment, Conservation and Parks, within 15 days after receipt of this notice, require a hearing by the Tribunal. The Minister of the Environment, Conservation and Parks will place notice of your appeal on the Environmental Registry. Section 142 of the *Environmental Protection Act* provides that the notice requiring the hearing ("the Notice") shall state:

- a. The portions of the environmental compliance approval or each term or condition in the environmental compliance approval in respect of which the hearing is required, and;
- b. The grounds on which you intend to rely at the hearing in relation to each portion appealed.

The Notice should also include:

1. The name of the appellant;
2. The address of the appellant;
3. The environmental compliance approval number;
4. The date of the environmental compliance approval;
5. The name of the Director, and;
6. The municipality or municipalities within which the project is to be engaged in.

And the Notice should be signed and dated by the appellant.

This Notice must be served upon:

Registrar\*  
Ontario Land Tribunal  
655 Bay Street, Suite 1500  
Toronto, Ontario  
M5G 1E5  
OLT.Registrar@ontario.ca

and

The Minister of the Environment,  
Conservation and Parks  
777 Bay Street, 5th Floor  
Toronto, Ontario  
M7A 2J3

and

The Director appointed for the purposes of  
Part II.1 of the *Environmental Protection Act*  
Ministry of the Environment,  
Conservation and Parks  
135 St. Clair Avenue West, 1st Floor  
Toronto, Ontario  
M4V 1P5

**\* Further information on the Ontario Land Tribunal's requirements for an appeal can be obtained directly from the Tribunal at: Tel: (416) 212-6349 or 1 (866) 448-2248, or [www.olt.gov.on.ca](http://www.olt.gov.on.ca)**

This instrument is subject to Section 38 of the *Environmental Bill of Rights*, 1993, that allows residents of Ontario to seek leave to appeal the decision on this instrument. Residents of Ontario may seek leave to appeal within 15 days from the date this decision is placed on the Environmental Registry. By accessing the Environmental Registry at

<https://ero.ontario.ca/>, you can determine when the leave to appeal period ends.

The above noted activity is approved under s.20.3 of Part II.1 of the *Environmental Protection Act*.

DATED AT TORONTO this 9th day of February, 2026



---

Nancy E Orpana, P.Eng.

Director

appointed for the purposes of Part II.1 of the  
*Environmental Protection Act*

AK/

c: District Manager, MECP York-Durham  
Roxana Ungureanu, BCX Environmental Consulting